

Multisite Encoder E2211, Rev. 2



Product Overview

Single and Dual Channel Video Encoder. Capable of streaming (1) UHD/4K video, or (2) 1080p60 videos, with up to 16 channels of audio

Production Audio/Video Input

- Connections** (2) 10 bit 6G-SDI & (2) HDMI 2.0a. Input can be either SDI or HDMI, set in software. Only one type of capture interface is enabled at a time (two SDI or two HDMI). Accepts 16 channels of 24-bit 48 kHz embedded audio on video input #1.
- Format Types** SD: 525i59.94 NTSC, 625i50 PAL
HD: 720p50, 720p59.94, 720p60, 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60, 1080i50, 1080i59.94, 1080i60
UHD: 2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30
- SDI Compliance** SMPTE 259M, 292M, 424M, ST-2081

Compression for Streaming

- Video Codec** HEVC / H.265 (MPEG-H Part 2), H.264 (MPEG-4 AVC)
- Audio Codec** AAC-LC with 1, 2, 5.1, 8, or 16 channels of audio

General Specifications

- Monitor interface** No monitor required. Supplied with a DVI-D emulator (installed).
- Network Interface** (2) Gigabit Ethernet LAN
- Storage Capacity** 256GB SSD (~230 GB available); 150+ TB Written (TBW) Endurance
- Misc. Ports** No keyboard or mouse required. (1) PS/2 Mouse/Keyboard Port
- Dimensions** Rackmount 2U, 19.0" (W) x 15.5" (D) x 3.5" (H); 21 lbs
- Power** 100V - 240V Input, 520W maximum draw, redundant hot swappable modules
- Warranty** 1 Year Limited Manufacturer's Warranty.
- Manufactured** U.S.A