

S112V

- 12" high power woofer
- 2" titanium compression driver
- Integral pole socket for stand mounting
- Perfect for small bands



C115VA & C112VA

- Flying versions of C112V and C115V
- 12 integral fly points
- Terminal strip for easy wiring
- Eye bolts included
- Ready to hang



C112V

- 12" 2-way design
- High-power woofer
- Titanium HF driver
- Integral pole socket for stand mounting
- Great for vocals

S215V

- Dual 15" cast frame woofers
- 2000-watt peak power handling
- Tightly braced cabinet
- Excellent high-output performer



SW218V

- Dual 18" subwoofer
- Cast frame drivers
- 2400-watt peak power handling
- Amazing bass performance

CW218V

- Dual 18" subwoofer
- Unique folded baffle design
- Low-profile cabinet
- Capable of extreme SPL



C L U B Y



S E R I E S

C SERIES

C215V

- Two 15" cast frame woofers
- 2000-watt peak power handling
- 90 x 45 degree CD horn
- Perfect where high sound pressure levels are required

CM10V

- 10" floor monitor
- 1" titanium dome compression driver
- Can also be used as a main speaker
- Pole socket allows use as a main speaker
- Great where size is a concern

CM12V

- 12" 2-way floor monitor
- 2" titanium HF driver
- Rugged, low-profile design
- Pole socket allows use as a main speaker
- Great for vocals

C115V

- 15" cast frame woofer
- 1000 watt peak power handling
- 90 x 45 degree CD horn
- Integral pole socket for stand mounting
- Excellent for live and recorded music

CW115V

- 15" cast frame driver
- Efficient bass-reflex design
- Integral socket for main speaker mounting
- Solid response down to 35Hz

CM15V

- 15" 2-way floor monitor
- Full frequency response
- Pole socket allows use as a main speaker
- Very high output

CM118V

- 18" cast frame driver
- 1200 watt peak power handling
- Bass reflex design
- Integral socket for main speaker mounting
- Great for use with dance music



Club V loudspeakers with the C prefix are coated with a heavy-duty elastomeric spray coating. Designed as an installation alternative to the carpeted S versions, they can easily fit any décor. The finish is very tough, and readily paintable to match surroundings. The steel grilles are foam-lined with acoustically transparent material to provide a more subdued appearance.

YAMAHA CLUB V SERIES SPECS

| Model | Woofer | Tweeter (diaphragm) | Frequency Response (-10dB) | Nominal Impedance | Power Handling (noise ¹ /program/peak) | Sensitivity 1W, 1m | Maximum SPL ³ | Dimensions ² W x H x D | Weight ² (pounds) |
|---|---------|------------------------|-------------------------------|----------------------|--|-----------------------|-----------------------------|--------------------------------------|---------------------------------|
| S SERIES Road-worthy, rugged carpet covered models | | | | | | | | | |
| S112V | 12" | 2" titanium | 60Hz–16kHz | 8Ω | 175 / 350 / 700 | 97dB | 126dB | 17 x 25 x 13 | 42.5 |
| S115V | 15" | 2" titanium | 55Hz–16kHz | 8Ω | 250 / 500 / 1000 | 99dB | 129 | 19 x 28 x 15 | 60.5 |
| S215V | 15" (2) | 2" titanium | 42Hz–16kHz | 4Ω | 500 / 1000 / 2000 | 99dB | 132 | 20 x 46 x 24 | 101.0 |
| SM10V | 10" | 1" phenolic | 70Hz–20kHz | 8Ω | 125 / 250 / 500 | 96dB | 123 | 22 x 14 x 11 | 27.0 |
| SM12V | 12" | 2" titanium | 60Hz–16kHz | 8Ω | 175 / 350 / 700 | 97dB | 126 | 25 x 16 x 14 | 43.0 |
| SM15V | 15" | 2" titanium | 55Hz–16kHz | 8Ω | 250 / 500 / 1000 | 99dB | 129 | 28 x 19 x 13 | 57.0 |
| SW115V | 15" | n/a | 35Hz–2kHz | 8Ω | 250 / 500 / 1000 | 95dB | 125 | 19 x 24 x 21 | 64.0 |
| SW118V | 18" | n/a | 30Hz–2kHz | 8Ω | 300 / 600 / 1200 | 96dB | 127 | 22 x 32 x 25 | 71.0 |
| SW218V | 18" (2) | n/a | 30Hz–2kHz | 4Ω | 600 / 1200 / 2400 | 98dB | 132 | 48 x 23 x 26 | 132.0 |

| | | | | | | | | | |
|---|---------|-------------|------------|----|-------------------|------|-----|--------------|-------|
| C SERIES Durable spray-finished models with foamed steel grilles | | | | | | | | | |
| C112V | 12" | 2" titanium | 60Hz–16kHz | 8Ω | 175 / 350 / 700 | 97dB | 126 | 17 x 25 x 13 | 42.5 |
| C115V | 15" | 2" titanium | 55Hz–16kHz | 8Ω | 250 / 500 / 1000 | 99dB | 129 | 19 x 28 x 15 | 60.5 |
| C215V | 15" (2) | 2" titanium | 42Hz–16kHz | 4Ω | 500 / 1000 / 2000 | 99dB | 132 | 20 x 46 x 24 | 101.0 |
| CM10V | 10" | 1" phenolic | 70Hz–20kHz | 8Ω | 125 / 250 / 500 | 96dB | 123 | 22 x 14 x 11 | 27.0 |
| CM12V | 12" | 2" titanium | 60Hz–16kHz | 8Ω | 175 / 350 / 700 | 97dB | 126 | 25 x 16 x 14 | 43.0 |
| CM15V | 15" | 2" titanium | 55Hz–16kHz | 8Ω | 250 / 500 / 1000 | 99dB | 129 | 28 x 19 x 13 | 57.0 |
| CW115V | 15" | n/a | 35Hz–2kHz | 8Ω | 250 / 500 / 1000 | 95dB | 125 | 19 x 24 x 21 | 64.0 |
| CW118V | 18" | n/a | 30Hz–2kHz | 8Ω | 300 / 600 / 1200 | 96dB | 127 | 22 x 32 x 25 | 71.0 |
| CW218V | 18" (2) | n/a | 30Hz–2kHz | 4Ω | 600 / 1200 / 2400 | 98dB | 132 | 48 x 23 x 26 | 132.0 |

| | | | | | | | | | |
|---|-----|-------------|------------|----|------------------|------|-----|--------------|------|
| FLYABLE MODELS Ideal for installations | | | | | | | | | |
| C112VA | 12" | 2" titanium | 60Hz–16kHz | 8Ω | 175 / 350 / 700 | 97dB | 126 | 17 x 25 x 13 | 42.5 |
| C115VA | 15" | 2" titanium | 55Hz–16kHz | 8Ω | 250 / 500 / 1000 | 99dB | 129 | 19 x 28 x 15 | 60.5 |

¹ Per IEC RS-426 specifications. ² Dimensions and weight are approximate. ³ Calculated.



CCI Solutions
be seen. be heard.

For more information or to order call
1-800-426-8664 or visit **www.ccisolutions.com**