


## DeckLink Mini Recorder



**\$145**

Record uncompressed 10-bit video from SDI and HDMI video sources. DeckLink Mini Recorder switches between SD and HD video formats and is perfect for building ingest servers or other video solutions where you need to capture only in a low profile card! Includes two PCI Express shields for both full height and low profile slots.

### Connections

#### SDI Video Input

1 x 10-bit SD/HD switchable.

#### SDI Audio Input

8 channels embedded in SD and HD.

#### HDMI Video Input


1 x HDMI 1.4 type A connector.

#### HDMI Audio Input

8 Channels embedded in SD and HD.

#### Computer Interface

PCI Express 1 lane, compatible with 4, 8 and 16 lane PCI Express slots.



### Supported Codecs

AVC-Intra, AVCHD, Canon XF MPEG2,  
Digital SLR, DV-NTSC, DV-PAL,  
DVCPRO50, DVCPROHD, DPX, HDV,  
XDCAM EX, XDCAM HD, XDCAM  
HD422, DNxHR & DNxHD, Apple  
ProRes 4444, Apple ProRes 422 HQ,  
Apple ProRes 422, Apple ProRes LT,  
Apple ProRes 422 Proxy,  
Uncompressed 8-bit 4:2:2,  
Uncompressed 10-bit 4:2:2.

---

## Software

### Software Included

Media Express, Disk Speed Test, LiveKey, Blackmagic Desktop Video Utility and Blackmagic driver on Mac OS and Windows. Media Express, Blackmagic Desktop Video Utility and Blackmagic driver on Linux.

### Internal Software Upgrade

Firmware built into software driver. Loaded at system start or via updater software.

### Physical Installation

PCI Express 1 lane, compatible with 1, 4, 8 and 16 lane PCI Express slots on Mac OS, Windows and Linux. Mac systems require a Mac Pro computer with PCI Express slots. Please check the Support pages to see the full system requirements.

---

## Software Applications



DaVinci Resolve



Adobe Premiere Pro CC



Avid Media Composer



Adobe Photoshop CC



Media Express

### Other supported applications include:

Tools On Air Just: Play & Live & In, Softron MovieRecorder & MReplay, Adobe Flash Media Live Encoder, Telestream Wirecast, Livestream Producer, Resolume Arena, Magix Vegas Pro & Movie Edit Pro Premium, Corel VideoStudio Pro, CyberLink PowerDirector, Vidblaster X & Studio & Broadcast, Uniplay One & CG, CasparCG Server, Magicsoft CG, Xsplit Broadcaster, Imagine Communications Velocity & InfoCaster, DevTek Easy Media Suite, Metus Ingest, Boinx Software MimoLive, Cinegy Capture Pro, vMix Live, Renewed Vision ProPresenter, Ventuz Director, Class X Liveboard & Coral CG, Glookast Capturer, Open Broadcaster Software Studio, Nautilus NEMO3D.

---

## Video Standards

### SD Video Standards

525i59.94 NTSC, 625i50 PAL

---

**HD Video Standards**

720p50, 720p59.94, 720p60  
1080p23.98, 1080p24, 1080p25,  
1080p29.97, 1080p30, 1080PsF23.98,  
1080PsF24, 1080PsF25,  
1080PsF29.97, 1080PsF30  
1080i50, 1080i59.94, 1080i60

**SDI Compliance**

SMPTE 259M and 292M.

**SDI Metadata Support**

RP 188/SMPTE 12M-2 and closed  
captioning.

**Audio Sampling**

Television standard sample rate of 48  
kHz and 24 bit.

**Color Precision**

8-bit & 10-bit.

**Video Sampling**

YUV 4:2:2.

**Color Space**

REC 601, REC 709.

**Multiple Rate Support**

SDI and HDMI are switchable  
between standard definition and high  
definition.

**Copy Protection**

HDMI input is unable to capture from  
copy protected HDMI sources. Always  
confirm copyright ownership before  
capture or distribution of content.

---

## Processing

**Colorspace Conversion**

Hardware based real time.

**HD to SD Down Conversion**


Software based down conversion  
during video capture.

**HD Up Conversion**

Software based up conversion from  
SD to 720HD or 1080HD on capture.  
Selectable between 4:3 pillarbox or  
16:9 anamorphic.

---

## Physical Specifications



1.98 oz

---

## Operating Systems



Mac OS X 10.11 El Capitan,  
macOS 10.12 Sierra,  
macOS 10.13 High Sierra or later.



Windows 7, 8.1 and 10, all 64-bit.



Linux

---

## Power Requirements

### Power Consumption

5 Watts

---

## EMC Certifications

FCC, CE and C-Tick.

---

## Environmental Specifications

### Operating Temperature

5° to 40° C (32° to 104° F)

### Storage Temperature

-20° to 45° C (-4° to 113° F)

### Relative Humidity

0% to 90% non-condensing

---

## What's Included

DeckLink Mini Recorder  
Low profile slot bracket  
SD card with software and manual

---

## Warranty

### 3 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2018, all rights reserved.

All trademarks are property of their respective owners. MSRP excludes sales taxes/duties and shipping costs.

This website uses remarketing services to advertise on third party websites to previous visitors to our site.

You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller